Purificn. of air by scrubbing with activated sludge and solvent - using membrane filtration to separate sludge and solvent from purge stream. L20 ANSWER 100 OF 121 WPINDEX COPYRIGHT 2002 DERWENT INFORMATION LTD 1992-332844 [41] WPINDEX DNC C1992-148016 DC D15 J01 BLUM, S; KRATZ, G; YUEKSEL, M L; YUEKSEL, M (HENK) HENKEL KGAA CYC 17 A 19921001 (199241)* PΤ DE 4109732 4 p WO 9216283 Al 19921001 (199242) DE 17p RW: AT BE CH DE DK ES FR GB GR IT LU MC NL SE W: CA US EP 579623 Al 19940126 (199404) DE R: AT BE CH DE DK ES FR GB GR IT LI LU NL SE EP 579623 B1 19950315 (199515) DE R: AT BE CH DE DK ES FR GB GR IT LI LU NL SE G 19950420 (199521) DE 59201674 ES 2069419 T3 19950501 (199524) DE 4109732 A DE 1991-4109732 19910325; WO 9216283 A1 WO 1992-EP566 19920316; EP 579623 A1 EP 1992-906671 19920316, WO 1992-EP566 19920316; EP 579623 B1 EP 1992-906671 19920316, WO 1992-EP566 19920316; DE 59201674 G DE 1992-501674 19920316, EP 1992-906671 19920316, WO 1992-EP566 19920316; ES 2069419 T3 EP 1992-906671 19920316 FDT EP 579623 A1 Based on WO 9216283; EP 579623 B1 Based on WO 9216283; DE 59201674 G Based on EP 579623, Based on WO 9216283; ES 2069419 T3 Based on EP 579623 PRAI DE 1991-4109732 19910325 AN 1992-332844 [41] WPINDE WPINDEX 4109732 A UPAB: 19931006 Purificn. of air contg. water-insol. biodegradable contaminants is effected by scrubbing the air with a mixt. of activated sludge (AS) and a high-boiling solvent, whereby the solvent absorbs the contaminants and the AS degrades them. The solvent and AS are sepd. from at least part of the scrubber effluent (and recycled), while the residual effluent is discharged. Sepn. is effected by membrane filtration using an inorganic or hydrophilised organic membrane.

ADVANTAGE - Membrane filtration gives cleaner

sepn. than flotation (cf. DE3641442).